

#### SMOKE ALARM WITH TEN-YEAR **NON-REPLACEABLE LITHIUM POWERCELL** Model SA340

#### IMPORTANT! PLEASE READ CAREFULLY AND SAVE.

This user's manual contains important information about your Smoke Alarm's operation If you are installing this Smoke Alarm for use by others, you must leave this manual-or a copy of it-with the end user.



Model SA340

M08-0143-002 **J1** 05/07

### INTRODUCTION

Thank you for choosing First Alert® for your Smoke Alarm needs. You have purchased a state-of-the-art Smoke Alarm designed to provide you with early warning of a fire. Please take the time to read this manual and make the Smoke Alarm an integral part of your family's safety plan. Key Features of the SA340 Smoke Alarm

Tamper Resistant Lithium Powercell: Provides continuous power for up to 10 years. Powercell cannot be removed. Single Test/Silence Button: Allows you to test the Alarm or silence

nuisance alarms. Testing the Alarm assures you that the unit is functioning correctly and ready to protect you and your family. The Alarm can be silenced for up to 10 minutes in the event of a nuisance alarm. Low power warning: The Alarm will sound a "chirp" once per minute

when the Alarm reaches the end of its service life and needs to be

Blinking Power Indicator: Confirms that the Smoke Alarm is receiving

© 2007 BRK Brands, Inc., a subsidiary of Jarden Corporation.

3901 Liberty Street Road, Aurora, IL 60504-8122 All rights reserved. Consumer Affairs: (800) 323-9005 • www.firstalert.con

All First Alert® Smoke Alarms conform to regulatory requirements, including UL217 and are designed to detect particles of combustion Smoke particles of varying number and size are produced in all fire lonization technology is generally more sensitive than photoelectric technology at detecting small particles, which tend to be produced in greater amounts by flaming fires, which consume combustible materials rapidly and spread quickly. Sources of these fires may include paper burning in a wastebasket, or a grease fire in the kitchen

Photoelectric technology is generally more sensitive than ionization Photoelectric technology is generally more sensitive that nonleaded technology at detecting large particles, which tend to be produced in greater amounts by smoldering fires, which may smolded the sensitive flower of those fires may include the sensitive flower of the s for hours before bursting into flame. Sources of these fires may include cigarettes burning in couches or bedding.

For maximum protection, use both types of Smoke Alarms on each

level and in every bedroom of your home.

## FIRE SAFETY TIPS

Follow safety rules and prevent hazardous situations: 1) Use smoking materials properly. Never smoke in bed. 2) Keep matches or lighters away from children; 3) Store flammable materials in proper containers 4) Keep electrical appliances in good condition and don't overload electrical circuits; 5) Keep stoves, barbecue grills, fireplaces and chimneys grease- and debris-free; 6) Never leave anything cooking on the stove unattended; 7) Keep portable heaters and open flames, like candles, away from flammable materials; 8) Don't let rubbish accumulate. Keep alarms clean, and test them weekly. Replace alarms immediately if they are not working properly. Smoke Alarms that do not work cannot aler you to a fire. Keep at least one working fire extinguisher on every floor, and an additional one in the kitchen. Have fire escape ladders or other reliable means of escape from an upper floor in case stairs are blocked.

## **BEFORE YOU INSTALL THIS SMOKE ALARM**

**IMPORTANT!** Read "Recommended Locations for Smoke Alarms and "Locations to Avoid for Smoke Alarms" before beginning. This unit monitors the air, and when smoke reaches its sensing chamber, it alarms. It can give you more time to escape before fire spreads. This unit can ONLY give an early warning of developing fires if it is installed, maintained and located where smoke can reach it, and where all residents can hear it, as described in this manual. This unit will not sense gas, heat, or flame. It cannot prevent or extinguish fires.

Understand The Different Type of Smoke Alarms Battery powered or electrical? Different Smoke Alarms provide

different types of protection. See "About Smoke Alarms" for details Know Where To Install Your Smoke Alarms

Fire Safety Professionals recommend at least one Smoke Alarm on every level of your home, in every bedroom, and in every bedroom hallway or separate sleeping area. See "Recommended Locations For Smoke Alarms" and "Locations To Avoid For Smoke Alarms" for

Know What Smoke Alarms Can and Can't Do

A Smoke Alarm can help alert you to fire, giving you precious time to escape. It can only sound an alarm once smoke reaches the sensor. See "Limitations of Smoke Alarms" for details.

## Check Your Local Building Codes

This Smoke Alarm is designed to be used in a typical single-family home. It alone will not meet requirements for boarding houses, apartment buildings, hotels or motels. See "Special Compliance Considerations" for details.

This unit will not alert hearing impaired residents. It is recommended that you install special units which use devices like flashing strobe lights to alert the hearing impaired residents. Do not connect this unit to any other alarm or auxiliary device. It is a single-station unit that cannot be linked to other devices. Connecting anything else to this unit may prevent it from working properly.


This Smoke Alarm cannot detect smoke until you activate it. You must activate the unit for it to receive power from the powercell. Failure to activate the unit will prevent the alarm from providing any warning of smoke or fire.

The powercell in this unit cannot be replaced—once it reaches the end of its service life, you must install a new Smoke Alarm. You must deactivate the unit before disposing of it.

## ACAUTION!

- Do not install this unit over an electrical junction box. Air currents around junction boxes can prevent smoke from reaching the sensing chamber and prevent the unit from alarming. Only AC powered units are intended for installation over junction boxes.
- Do not stand too close to the unit when the alarm is sounding. It is loud to wake you in an emergency. Exposure to the horn at close range may harm your hearing.
- Do not paint over the unit. Paint may clog the openings to the sensing chamber and prevent the unit from operating properly.

## **HOW TO INSTALL THIS SMOKE ALARM** THE PARTS OF THIS SMOKE ALARM



1. Test/Silence button 2. Power/alarm indicator LED

**TOOLS YOU WILL NEED:** This unit is designed to be mounted on the ceiling, or on the wall if necessary.

- Pencil • Drill with 3/16" (5 mm)
- · Standard flathead

Hammer

. Mounting bracket 2. Mounting slots

5. Turn to attach to bracket



3. Powercell 4. Deactivation Tab (located under labe

i. Turn this way to remove from bracket

## **FOLLOW THESE SIMPLE STEPS!**

## **INSTALL THE MOUNTING BRACKET:**

To remove the mounting bracket from the base firmly and twist the mounting bracket

- Place the bracket on the wall or ceiling where you want to mount the alarm.
- Hold the mounting bracket against the ceiling (or wall) and trace around the inside of the two
- Make a mark inside each outline for the drill holes.
- 5. Put the unit where it won't get covered with dust when you drill the mounting holes.
- 6. Using a 3/16-inch (5 mm) drill bit, drill a hole through each pencil mark.
- Insert the plastic screw anchors (in the plastic bag with screws) into the holes. Tap the screw anchors gently with a hammer, if necessary, until they are flush with the ceiling or wall.
- Line the mounting bracket up over the plastic screw anchors.
- 9. Screw the mounting bracket to the ceiling or wall through the mounting slots using the two screws provided.
- 10. Tighten both screws all the way.

## **INSERTING THE POWERCELL:**

#### AWARNING! You must activate the powercell before attaching the Smoke Alarm to the bracket.

- 1. Turn Alarm upside down. Line up the pins and snap the powercell into the Alarm.
- 2. The powercell cannot be removed after it is locked into the Alarm If you have trouble activating the unit, call Consumer Affairs at: 1-800-323-9005 for assistance.
- 3. Test the Smoke Alarm. Press and hold the test button on the cover of the unit until the alarm sounds (the unit may continue to alarm for a few seconds after you release the button).

  During testing, you will hear a loud, repeating horn pattern. 3 beeps, pause, 3 beeps, pause. If the unit does not alarm during testing, call Consumer Affairs for assistance.

#### ATTACH SMOKE ALARM TO MOUNTING BRACKET

- Line up the alignment tab on the unit with the alignment tab on the mounting bracket. Push the unit toward the bracket, and turn it clockwise until you feel it snap into place.
- 2. Test the unit again. Press the test button until the horn begins sounding. During testing, you will hear a loud, repeating horn pattern: 3 beeps, pause, 3 beeps, pause.

## **WEEKLY TESTING**

## AWARNING!

- NEVER use an open flame of any kind to test this unit. You might accidentally damage or set fire to the unit or to your home. The built-in test switch accurately tests the unit's operation as required by Underwriters Laboratories, Inc. (UL).
- If the Alarm ever fails to test properly, replace it immediately. Products under warranty may be returned to the manufacturer for replacement. See "Limited Warranty".

#### ACAUTION!

DO NOT stand close to the Alarm when the horn is sounding Exposure at close range may be harmful to your hearing. When testing, step away when horn starts sounding.

It is important to test this unit every week to make sure it is working **properly.** Using the test button is the recommended way to test this Smoke Alarm. Press and hold the test button on the cover of the unit until the alarm sounds (the unit may continue to alarm for a few seconds after you release the button). During testing you will hear a loud, repeating horn pattern: 3 beeps, pause, 3 beeps, pause. Red LED

## REGULAR MAINTENANCE

This unit has been designed to be as maintenance free as possible, but there are a few simple things you must do to keep it working properly.

- Test it at least once a week.
- Clean the Smoke Alarm at least once a month; gently vacuum the outside of the Smoke Alarm using your household vacuum's soft brush attachment. A can of clean compressed air (sold at computer or office supply stores) may also be used. Follow manufacturer instructions for use. Test the Smoke Alarm. Never use water, cleaners or solvents since they may damage the unit.
- If the Smoke Alarm becomes contaminated by excessive dirt, dust and/or grime, and cannot be cleaned to avoid unwanted alarms, replace the unit immediately.
- Relocate the unit if it sounds frequent unwanted alarms. See "Locations to Avoid For Smoke Alarms" for details.


When the powercell becomes weak, the Smoke Alarm unit will "chirp" about once a minute (the low power warning). This low power warning should last for 30 days, but you should replace the Smoke Alarm immediately to continue your protection.

# TO PERMANENTLY DEACTIVATE THE SMOKE ALARM

Alarm is sealed. The powercell is not replaceable. Once it reaches the end of its service life, or after 10 years—whichever comes first vou must install a new Smoke Alarm.

After 10 years or after the "low power warning" sounds (whichever

- 1. Once you deactivate this unit, it will not detect smoke or alarm. It cannot be reactivated. You must install a new unit to continue your protection. Alarm will resist mounting to the bracket after
- 2. Use a flathead screwdriver to score label along dotted line.
- 3. Use thumb to pull deactivation tab outward until tab snaps into place. This will discharge the powercel and deactivate the unit.
- 4. Install a new Smoke Alarm



## IF THIS SMOKE ALARM SOUNDS **RESPONDING TO AN ALARM**

During an alarm, you will hear a loud, repeating horn pattern: 3 beeps, pause, 3 beeps, pause. Red LED flashes.

#### AWARNING!

- If the unit alarms get everyone out of the house immediately.
- . If the unit alarms and you are not testing the unit, it is warning erous situation that requires you mmediate attention. NEVER ignore any alarm. Ignoring the alarm may result in injury or death.
- Use the Silence feature to stop an unwanted alarm (caused by cooking smoke, etc.), then open a window or fan the smoke away from the unit. The Smoke Alarm will reset automatically.

## WHAT TO DO IN CASE OF FIRE

- Don't panic; stay calm. Follow your family escape plan.
- Get out of the house as quickly as possible. Don't stop to
- get dressed or collect anything.
- Feel doors with the back of your hand before opening them. If a door is cool, open it slowly. Don't open a hot door, Keep doors and windows closed, unless you must escape through them
- Cover your nose and mouth with a cloth (preferably damp). Take short, shallow breaths.
- Meet at your planned meeting place outside your home, and do a head count to make sure everybody got out safely.
- Call the Fire Department as soon as possible from outside.
- Give your address, then your name. Never go back inside a burning building for any reason
- Contact your Fire Department for ideas on making your home safer.

#### AWARNING! Alarms have various limitations. See "Limitations of Smoke Alarms"

**USING THE SILENCE FEATURE** The Silence Feature can temporarily quiet an unwanted alarm for up to 10 minutes. To use this feature, press the "Test/Silence" button. The Alarm remains functional. The LED will flash every 10 seconds (for up to 10 minutes) to remind you the alarm has been silenced. The flashing

#### LED will stop when the unit returns to normal operation. AWARNING!

The Silence Feature does not disable the unit—it makes it temporar ily less sensitive to smoke. For your safety, if smoke around the unit is dense enough to suggest a potentially dangerous situation, it will stay in alarm, or may re-alarm quickly. If you do not know the source of the smoke, do not assume it is an unwanted alarm. Not ing to an alarm can result in property loss, injury or death.

Smoke Alarms may not operate properly because of a dead or weak powercell, a build-up of dirt, dust or grease on the Smoke Alarm cover. or installation in an improper location. Clean the Smoke Alarm as described in "Regular Maintenance," and test the Smoke Alarm again. If it fails to test properly when you use the test button, or if the problem persists, replace the Smoke Alarm immediately.

IF YOU SUSPECT A PROBLEM

- If you experience frequent non-emergency alarms (like those caused by cooking smoke), try relocating the Smoke Alarm.
- If the alarm sounds when no smoke is visible, try cleaning o relocating the Smoke Alarm. The cover may be dirty.
- If the alarm no longer sounds during testing, replace the Smoke Alarm! If the Smoke Alarm was properly activated, and had previously alarmed during testing, the powercell is at the end of its service life. (See "Regular Maintenance.")
- If the alarm will not silence when you use the Silence feature, DO NOT IGNORE THE ALARM! This indicates a potentially
- If the Smoke Alarm "chirps" about once a minute (for more than 30 minutes), Replace the Smoke Alarm! (See "Regular Maintenance.") This is the low power warning.

### DO NOT TRY FIXING THE ALARM YOURSELF—THIS WILL VOID YOUR WARRANTY!

If the Smoke Alarm is still not operating properly, and it is still under warranty, please see "How to Obtain Warranty Service" in the Limited

#### LIMITED WARRANTY

BRK Brands, Inc., ("BRK") the maker of First Alert® brand products warrants that for a period of ten years from the date of purchase, this product will be free from defects in material and workmanship. BRK, at its option, will repair or replace this product or any component of the product found to be defective during the warranty period. Replacement will be made with a new or remanufactured product or component. If the product is no longer available, replacement may be made with a ilar product of equal or greater value. This is your exclusive warranty. This warranty is valid for the original retail purchaser from the date of initial retail purchase and is not transferable. Keep the original sales receipt. Proof of purchase is required to obtain warranty performance BRK dealers, service centers, or retail stores selling BRK products do not have the right to alter, modify or any way change the terms and conditions of this warranty.

This warranty does not cover normal wear of parts or damage resulting from any of the following: negligent use or misuse of the product, use of improper voltage or current, use contrary to the operating instructions, disassembly, repair or alteration by anyone other than BRK or an authorized service center. Further, the warranty does not cover Acts of God, such as fire, flood, hurricanes and tornadoes or any batteries that are included with this unit.

BRK shall not be liable for any incidental or consequential damages caused by the breach of any express or implied warranty. Except to the extent prohibited by applicable law, any implied warranty of merchantability or fitness for a particular purpose is limited in duration to the duration of the above warranty. Some states, provinces or jurisdictions do not allow the exclusion or limitation of incidental or consequential damages or limitations on how long an implied warranty lasts, so the above limitations or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights that vary from state to state or province to province.

**How to Obtain Warranty Service** Service: If service is required, do not return the product to your retailer n order to obtain warranty service, contact the Consumer Affairs Division at 1-800-323-9005, 7:30 AM - 5:00 PM Central Standard Time, Monday through Friday. To assist us in serving you, please have the model number and date of purchase available when calling.

For Warranty Service return to:

BRK Brands, Inc., 25 Spur Drive, El Paso, TX 79906 This Smoke Alarm is designed to operate for 10 years, and is backed by a 10-year limited warranty. To date, the actual alarm, however, has not been tested for 10 years. The powercell in this Smoke Alarm is not replaceable. When it reaches the end of its service life, you must replace the entire Smoke Alarm to continue your protectio

## **RECOMMENDED LOCATIONS FOR SMOKE ALARMS**

Installing Smoke Alarms in Single-Family Residences The National Fire Protection Association (NFPA), recommends one Smoke Alarm on every floor, in every sleeping area, and in every bedroom. In new construction, the Smoke Alarms must be AC powered and interconnected. See "Agency Placement Recommendations" for details. For additional coverage, it is recommended that you install a Smoke Alarm in all rooms, halls, storage areas, finished attics, and basements, where temperatures normally remain between 40° F (4° C) and 100° F (38° C). Make sure no door or other obstruction could keep


#### smoke from reaching the Smoke Alarms. More specifically, install Smoke Alarms:

meters) long, install an alarm at each end.

- On every level of your home, including finished attics and basements Inside every bedroom, especially if people sleep with the door partly
- In the hall near every sleeping area. If your home has multiple sleeping areas, install a unit in each. If a hall is over 40 feet (12
- At the top of the first-to-second floor stairway, and at bottom of

## **IMPORTANT!**

Specific requirements for Smoke Alarm installation vary from state to state and from region to region. Check with your local Fire Department for current requirements in your area. It is recommended AC or AC/DC units be interconnected for added protection.



## For minimum security install one Smoke Alarm as close to each sleeping area as possible. For more security, but one unit in each room. Many older mobile homes (especially those built before 1978) have little or no insulation. If your mobile home is not well insulated, or if you are unsure

**INSTALLING SMOKE ALARMS IN MOBILE HOMES & RVS** 

of the amount of insulation, it is important to install units on inside walls only. Smoke Alarms should be installed where temperatures normally remain between 40° F (4° C) and 100° F (38° C). WARNING: Test units used in RVs after the vehicle has been in storage, before every trip, and once a week while in use. Failure to test units used in RVs as

### **AGENCY PLACEMENT RECOMMENDATIONS**

## NFPA 72 (National Fire Code) Chapter 11

"For your information, the National Fire Protection Association's Standard 72, reads as follows:

## "11.5.1 One- and Two-Family Dwelling Units."

described may remove your protection

"11.5.1.1 Smoke Detection. Where required by applicable laws, codes, or standards for the specified occupancy, approved single- and multiple -station Smoke Alarms shall be installed as follows: (1) In all sleeping rooms. Exception: Smoke Alarms shall not be required in sleeping rooms in existing one- and two-family dwelling units. (2) Outside of each separate sleeping area, in immediate vicinity of the sleeping rooms. (3) On each level of the dwelling unit, including basements Exception: In existing one- and two family dwelling units, approved Smoke Alarms powered by batteries are permitted.

"A.11.8.3 Are More Smoke Alarms Desirable? The required number of Smoke Alarms might not provide reliable early warning protection for those areas separated by a door from the areas protected by the required Smoke Alarms. For this reason, it is recommended that the householder consider the use of additional Smoke Alarms for those areas for increased protection. The additional areas include the basement, bedrooms, dining room, furnace room, utility room, and hallways not protected by the required Smoke Alarms. The installation of Smoke Alarms in kitchens, attics (finished or unfinished), or garages is not normally recommended, as these locations occasionally experience conditions that can result in improper operation."

#### California State Fire Marshal (CSFM)

Early warning detection is best achieved by the installation of fire detecion equipment in all rooms and areas of the household as follows: A Smoke Alarm installed in each separate sleeping area (in the vicinity, but outside bedrooms), and Heat or Smoke Alarms in the living rooms, dining rooms, bedrooms, kitchens, hallways, finished attics, furnace rooms, closets, utility and storage rooms, basements, and attached garages.

## **LOCATIONS TO AVOID FOR SMOKE ALARMS**

For best performance, AVOID installing Smoke Alarms in these areas:

- Where combustion particles are produced. Combustion particles form when something burns. Areas to avoid include poorly ventilated kitchens, garages, and furnace rooms. Keep units at least 20 feet (6 meters) from the sources of combustion particles (stove, furnace, water heater, space heater) if possible. In areas where a 20-foot (6 m) distance is not possible - in modular, mobile, or smaller homes, for example - it is recommended the Smoke Alarm be placed as far from these fuel-burning sources as possible. The placement recommendations are intended to keep these Alarms at a reasonable distance from a fuel-burning source, and thus reduce "unwanted" alarms. Unwanted alarms can occur if a Smoke Alarm is placed directly next to a fuel-burning source. Ventilate these areas as much as possible.
- In air streams near kitchens. Air currents can draw cooking smoke. into the sensing chamber of a Smoke Alarm near the kitchen.
- In very damp, humid or steamy areas, or directly near bathrooms with showers. Keep units at least 10 feet (3 meters) away from showers, saunas, dishwashers, etc.
- 100° F (38° C), including unheated buildings, outdoor rooms, porches, or unfinished attics or basements. In very dusty, dirty, or greasy areas. Do not install a Smoke Alarm

Where the temperatures are regularly below 40° F (4° C) or above

- directly over the stove or range. Clean a laundry room unit frequently to keep it free of dust or lint. Near fresh air vents, ceiling fans, or in very drafty areas. Drafts can
- blow smoke away from the unit, preventing it from reaching the sensing chamber.
- In insect infested areas. Insects can clog openings to the sensing chamber and cause unwanted alarms
- Less than 12 inches (305mm) away from fluorescent lights. Electrical "noise" can interfere with the sensor

## • In "dead air" spaces. "Dead air" spaces may prevent smoke from Avoiding Dead Air Spaces

"Dead air" spaces may prevent smoke from reaching the Smoke Alarm. To avoid dead air spaces, follow the installation recomme On ceilings, install Smoke Alarms as close to the center of the ceiling

as possible. If this is not possible, install the Smoke Alarm at least 4 inches (102 mm) from the wall or corner For wall mounting (if allowed by building codes), the top edge of Smoke Alarms should be placed between 4 inches (102 mm) and 12 inches (305

mm) from the wall/ceiling line, below typical "dead air" spaces On a peaked, gabled, or cathedral ceiling, install the first Smoke Alarm within 3 feet (0.9 meters) of the peak of the ceiling, measured horizontally. Additional Smoke Alarms may be required depending on the length, angle, etc. of the ceiling's slope. Refer to NFPA 72 for details on requirements for sloped or peaked ceilings.

# **ABOUT SMOKE ALARMS**

Battery or DC operated Smoke Alarms: Provide protection even ricity fails, provided the batteries or battery packs are fresh and correctly installed or activated. Units are easy to install, and do not require professional installation.

AC powered Smoke Alarms: Can be interconnected so if one unit senses smoke, all units alarm. They do not operate if electricity fails. AC with battery (DC) back-up: will operate if electricity fails, provided the batteries are fresh and correctly installed. AC and AC/DC units nust be installed by a qualified electrician. Smoke Alarms for Solar or Wind Energy users and battery backup

power systems: AC powered Smoke Alarms should only be operated with true or pure sine wave inverters. Operating this Smoke Alarm with most battery-powered UPS (uninterruptible power supply) products or square wave or "quasi sine wave" inverters **will damage the Alarm** If you are not sure about your inverter or UPS type, please consult with the manufacturer to verify. Smoke Alarms for the hearing impaired: Special purpose Smoke

Alarms should be installed for the hearing impaired. They include a visual alarm and an audible alarm horn, and meet the requirements of the Americans With Disabilities Act. Can be interconnected so if one

unit senses smoke, all units alarm. Smoke alarms are not to be used with detector guards unless the combination has been evaluated and found suitable for that purpose. All these Smoke Alarms are designed to provide early warning of fires in located, installed and cared for as described in the user's manual, and if smoke reaches them. If you are unsure which type of unit to install, refer to Chapter 2 of the National Fire Protection Association (NFPA) Standard 72 (National Fire Alarm Code) and NEPA 101 (Life Safety Code) National Fire Protection Association, One Batterymarch Park, Quincy, MA 02269-9101. Local building codes may also require specific units in new construction or in different areas of the home.

# **SPECIAL COMPLIANCE CONSIDERATIONS**

## AWARNING!

This Smoke Alarm alone is not a suitable substitute for complete fire detection systems in places housing many people—like apartment buildings, condominiums, hotels, motels, dormitories, hospitals, longterm health care facilities, nursing homes, day care facilities, or group homes of any kind—even if they were once single-family homes. It is not a suitable substitute for complete fire detection systems in warehouses, industrial facilities, commercial buildings, and special purpose non-residential buildings which require special fire detection and alarm systems. Depending on the building codes in your area, this Smoke Alarm may be used to provide additional protection in these

The following information applies to all four building types below In new construction, most building codes require the use of AC or AC/DC powered Smoke Alarms only. AC, AC/DC, or DC powered Smoke Alarms can be used in existing construction as specified by local building codes Refer to NFPA 72 (National Fire Alarm Code) and NFPA 101 (Life Safety Code), local building codes, or consult your Fire Department for detailed fire protection requirements in buildings not defined as "households."

## 1. Single-Family Residence:

Single family home, townhouse. It is recommended Smoke Alarms be installed on every level of the home, in every bedroom, and in each

#### 2. Multi-Family or Mixed Occupant Residence:

Apartment building, condominium. This Smoke Alarm is suitable for use in individual apartments or condos, provided a primary fire detection system already exists to meet fire detection requirements in common areas like lobbies, hallways, or porches. Using this Smoke Alarm in common areas may not provide sufficient warning to all residents or meet local fire protection ordinances/regulations.

## 3. Institutions:

Hospitals, day care facilities, long-term health care facilities. This Smoke Alarm is suitable for use in individual patient sleeping/resident rooms, provided a primary fire detection system already exists to meet fire detection requirements in common areas like lobbies, hallways, or porches. Using this Smoke Alarm in common areas may not provide sufficient warning to all residents or meet local fire protection ordinances /regulations.

## 4. Hotels and Motels:

Also boarding houses and dormitories. This Smoke Alarm is suitable for use inside individual sleeping/resident rooms, provided a primary fire detection system already exists to meet fire detection requirements in common areas like lobbies, hallways, or porches. Using this Smoke Alarm in common areas may not provide sufficient warning to all esidents or meet local fire protection ordinances/regulations

## **LIMITATIONS OF SMOKE ALARMS**

Smoke Alarms have played a key role in reducing deaths resulting from home fires worldwide. However, like any warning device, Smoke Alarms can only work if they are properly located, installed, and maintained, and if smoke reaches them. They are not foolproof.

Smoke alarms may not waken all individuals. Practice the escape plan at least twice a year, making sure that everyone is involved – from kids to grandparents. Allow children to master fire escape planning and practice before holding a fire drill at night when they are sleeping. If children or others do not readily waken to the sound of the smoke alarm, or if there are infants or family members with mobility limitations, make sure that someone is assigned to assist them in fire drill and in the event of an emergency. It is recommended that you hold a fire drill while family members are sleeping in order to determine their response to the sound of the smoke alarm while sleeping and to determine

whether they may need assistance in the event of an emergency. Smoke Alarms cannot work without power. DC operated units cannot work if the powercell is missing, deactivated, or dead, or if the powercell was not activated correctly. AC units cannot work if the AC power is cut off for any reason (open fuse or circuit breaker, failure along a power line or at a power station, electrical fire that burns the electrical wires, etc.). If you are concerned about the limitations of DC or AC power, install

both types of units. Smoke Alarms cannot detect fires if the smoke does not reach the Alarms. Smoke from fires in chimneys or walls, on roofs, or on the other side of closed doors may not reach the sensing chamber and set off the alarm. That is why one unit should be installed inside each bedroom or sleeping area—especially if bedroom or sleeping area doors are closed at night—and in the hallway between them.

Smoke Alarms may not detect fire on another floor or area of the dwelling. For example, a stand-alone unit on the second floor may not detect smoke from a basement fire until the fire spreads. This may not give you enough time to escape safely. That is why recommended minimum protection is at least one unit in every sleeping area, and every bedroom on every level of your dwelling. Even with a unit on every floor, stand-alone units may not provide as much protection as interconnected units, especially if the fire starts in a remote area. Some safety experts recommend installing interconnected AC powered units with battery back-up (see "About Smoke Alarms") or professional fire detection systems, so if one unit senses smoke, all units alarm Interconnected units may provide earlier warning than stand-alone

units since all units alarm when one detects smoke.

Smoke Alarms may not be heard. Though the alarm horn in this unit meets or exceeds current standards, it may not be heard if: 1) the unit is located outside a closed or partially closed door, 2) residents recently consumed alcohol or drugs, 3) the alarm is drowned out by noise from stereo, TV, traffic, air conditioner or other appliances, 4) residents are hearing impaired or sound sleepers. Special purpose units, like those with visual and audible alarms, should be installed for hearing impaired

Smoke Alarms may not have time to alarm before the fire itself

causes damage, injury, or death, since smoke from some fires may not reach the unit immediately. Examples of this include persons smoking in bed, children playing with matches, or fires caused by violent explosions resulting from escaping gas. Smoke Alarms are not foolproof. Like any electronic device, Smoke Alarms are made of components that can wear out or fail at any time. You must test the unit weekly to ensure your continued protection. Smoke Alarms cannot prevent or extinguish fires. They are not a substitute for property or life insurance.

Smoke Alarms have a limited life. The unit should be replaced immediately if it is not operating properly. You should always replace a Smoke Alarm after 10 years from date of purchase. Write the purchase date on the space provided on back of unit.

Replace Alarm 10 years after installation. Write the replacement date in the space provided on the Alarm label. For your records, please record: **Date Purchased:** Month/Year **Date Installed:** Replacement Date: Month/Year

First Alert® is a registered trademark of the First Alert Trust.

Printed in Mexico M08-0143-002 **J1** 05/07